

BSH - Sichtqualität, GL24 h nach DIN 1052,
wetterfest hell verleimt, gehobelt, gefast,
rechtwinklig gekappt.

StrathmannHolz

			BSH Fichte Si									eur. Lärche Si		Eiche Si (ETA)	
Querschnitt in mm		Stück/Hub	5,- m	7,- m	8,- m	10,- m	12,- m	14,- m	16,- m	18,- m	Zuschnitt	6,- m	12,- m	6,- m	12,- m
45	300	5					LA				LA				
60	100	18					LA				LA				
60	120	18								LA	LA	*	*		
60	140	12					LA				LA				
60	160	12		*						LA	LA	*	*	*	*
60	200	12		*						LA	LA	*	*	*	*
60	240	6		*						LA	LA			*	*
80	120	15								LA	LA				
80	140	10					LA				LA				
80	160	10	LA	*						LA	LA	*	*	*	*
80	180	10								LA	LA				
80	200	10	LA	*						LA	LA	*	*	*	*
80	240	5		*						LA	LA	*	*	*	*
80	280	5								LA	LA				
100	100	16								LA	LA	*	*	*	*
100	120	12					LA				LA				
100	160	8		*						LA	LA				
100	200	8		*						LA	LA				
100	240	4								LA	LA				
120	120	9	LA	*						LA	LA	*	*	*	*
120	160	6		*						LA	LA	*	*	*	*
120	200	6		*						LA	LA	*	*	*	*
120	240	3		*						LA	LA				
120	280	3		* (30 c)			LA	LA	LA	LA	LA				
120	320	3		* (30 c)			LA	LA	LA	LA	LA				
140	140	9		*						LA	LA				
140	200	6			*	*				LA	LA				
140	240	3			*	*	LA	LA	LA	LA	LA				
140	280	3			*	*	LA	LA	LA	LA	LA				
140	320	3					LA	LA	LA	LA	LA				
140	360	3					LA	LA	LA	LA	LA				
160	160	9					LA			LA	LA			*	*
160	200	6			*	*				LA	LA				
160	240	3			*	*	LA	LA	LA	LA	LA				
160	280	3					LA	LA	LA	LA	LA				
160	320	3					LA	LA	LA	LA	LA				
160	360	3					LA	LA	LA	LA	LA				
160	400	1					LA	LA	LA	LA	LA				
160	440	1						LA							
180	180	1								LA	LA				
200	200	1		*						LA	LA				
200	240	1		*			LA	LA	LA	LA	LA				
200	280	1					LA	LA	LA	LA	LA				
200	320	1			*		LA	LA	LA	LA	LA				
200	360	1					LA	LA	LA	LA	LA				
200	400	1					LA	LA	LA	LA	LA				
200	440	1						LA							

* = Lieferzeit ca. 1 Woche

